

2-CYCLE UNIVERSAL ENGINE OIL

SYNTHETIC BLEND WITH FUEL STABILIZER

TruSouth Universal 2-Cycle Engine Oil Synthetic Blend is blended from a mixture of high viscosity index paraffinic base stocks and Group III (synthetic) base oils. These oils are fortified with low-ash forming detergency additives, extreme pressure anti-wear components, a fuel stabilizer and a coupling agent to enhance oil-gasoline mixtures.

Designed for use in hot running, air-cooled engines such as chainsaws, lawnmowers, leaf blowers, string trimmers, and 2-cycle edgers and motorcycles. Can be mixed at any ratio up to 50:1. 6.4 ounces package size is designed to mix with 2.5 gallons at a 50:1 ratio or 2 gallons at a 40:1 ratio.

BENEFITS:

- Recommended for both homeowners and professional lawn care and tree cutting operations.
- Provides excellent cleanliness expected for genuine oils.
- Will not stain pistons.
- Contains a fuel stabilizer for additional fuel storage protection.
- Balanced components for optimum performance.
- Provides improved detergency.
- Smokeless.

INDUSTRY APPROVALS:

Meets and exceeds the following industry approvals:

- JASO FD/ ISO-EGD
- API TC
- TISI (Thailand Industry Standards Institute)

TYPICAL PROPERTIES

Test	Typicals
Viscosity, cSt @40C	36.8
Viscosity, cSt @100C	6.8
VI	140
API Gravity @60F	32.8
Flash, COC, C (F)	80 (182)
Pour, C (F)	-34 (29)
Color	Red

Order Numbers

Available in:	2-Cycle FD
12- 6.4 oz.	0126718
24- 2.6 oz.	0126744
55 gallons drums	0126711
and BULK	0126700