

WAY LUBE

TruSouth Way Lube products are formulated from highly refined, thermally stable, high viscosity index base stocks. These stocks are combined with carefully selected rust inhibitors, extreme pressure and demulsibility additives to provide premium protection and eliminate “stick-slip” jerky movements of sliding parts of machine tools.

TruSouth Way Lubricants provide high film strength, promote smooth tool motion, resist oxidation deterioration, and provide long service life.

BENEFITS:

- Ashless additive provides low environmental impact
- Robust Antiwear Performance
- Low Foaming
- Rapid Air Release
- Superior Demulsibility

INDUSTRY SPECIFICATIONS:

Meets the requirements of Cincinnati Machine P-47

TYPICAL PROPERTIES

Test	68	100	150	220	320
ISO Grade	68	100	150	220	320
Viscosity, cSt @40C	70.7	92	138	213.6	319
Viscosity, cSt @100C	7.2	8.9	11.4	19.1	20.1
VI	100	100	100	100	100
Flash, C (F)	206 (403)	218 (425)	218 (425)	212 (414)	260 (500)
Pour, C (F)	-41 (-42)	-41 (-42)	-26 (-15)	-26 (-15)	-26 (-15)

Order Numbers

Available in:	68	100	150	220	320
55 gallon drums	0173611	0173711	0173911	0173811	0174011
and BULK	0173600	0173700	0173900	0173800	0174000